

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION

Manufacture's Name: Pee Dee Ready Mix	Emergency Telephone Number: 843-407-5992
Address: 140 McLaoghin Rd. • Effingham, SC 29541	Trade Names: Ready Mixed Concrete
Chemical Family: 3CaO SiO ₂ (cement), 2Ca ₉ SiO ₂ (cement), 3 CaO Al ₂ O ₃ (cement), 4CaO Al ₂ O ₃ (cement), CaSO ₄ ·2H ₂ O. Traces CaO, MgO, K ₂ SO ₄ , No. 2504	

SECTION III - HAZARDOUS INGREDIENTS: Cement (Lime) & possible traces of hexavalent chromium & crystalline slice.

SECTION III - PHYSICAL DATA

Specific Gravity: 1.7 to 3.0 Solubility in Water: SLIGHTLY

Appearance and odor: Gray, plastic, flowable, granular, mud, odorless.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N.A. all sections

SECTION V - HEALTH HAZARD DATA

TLV: None Effects of overexposure: Dry skin and possible alkali burns (cement dermatitis).
Also possible traces of hexavalent chromium.

Emergency First Aid Procedures: Irrigate eyes with water. Wash affected areas of the body with soap and water.

SECTION VI - REACTIVITY DATA

X
Stability Unstable Conditions to Avoid: Product sets and hardens in 2 to 8 hrs. and is no longer hazardous.

Hazardous Polymerization Will Not Occur
X

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken In Case Material is Released or Spilled: Spill does not increase hazard.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Proactive Gloves: Yes, impervious Eye Protection: Yes, safety glasses with side shields or goggles

Other Protective Equipment: Use impervious, gloves, boots and clothing to protect skin from prolonged contact with plastic concrete.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storage: See above.

Other Precautions: Immediately after working with concrete, workers should shower with soap and water.

TERMS GOVERNING SALE OF CONCRETE

- Concrete is furnished according to Purchaser's specifications and contains the correct water content for strength of mix indicated. Added water decreases strength. If additional water or any other substances are added to the concrete at the job site by the Purchaser, or at his request, Pee Dee Ready Mix is no longer responsible for the slump, strength or quality of concrete.
- All concrete produced shall be in accordance with ASTM C-94 and no other warranty is made or implied. All sampling and testing shall be performed in accordance with ASTM standards.
- Terms of payment for customers with approved credit only: Net/10th proximo.
- Past due bills will be subject to a service charge of 1.5% per month on the unpaid balance.
- Pee Dee Ready Mix shall be entitled to recover reasonable attorney's fees and outside collection costs if such action is required to secure payment of amounts owed.
- Unloading time allowed is six (6) minutes per cubic yard with a maximum of one (1) hour per load. Delays of more than this time shall be subject to additional charge.
- The Purchaser agrees to provide suitable roadways or approaches to point of delivery beyond the curb line and on other than paved sheets. We reserve the right to stop deliveries if the roadways or approaches are unsatisfactory to us. If the Purchaser requests delivery beyond the curb line or other than paved sheets, Purchaser releases Pee Dee Ready Mix from liability for and Purchaser will hold Pee Dee Ready Mix harmless and indemnify Pee Dee Ready Mix against any liability for damage to the curb, sidewalk or any property of contractor of owner, or injury to any person whatsoever. If required, Purchaser agrees to assume cost and responsibility for a towing service utilized to remove Pee Dee Ready Mix delivery trucks from a soft, boggy or otherwise undriveable area.